GEES QUALITY STANDARD REMARKS FOR MRO

REMARK

SUBJECT / TEXT

QC-014 (Rev. B, 8/11/00)

SPOOLED WELD WIRE

SPOOLED WELD WIRE MUST MEET THE FOLLOWING REQUIREMNTS:

- 1) WELD WIRE MUST MEET AMS 2816 OR ARP 1876 REQUIREMENTS
- 2) WELD WIRE INDICATING REQUIREMENTS OF BOTH AMS 2813 AND AMS 2814 OR AMS 2814 ALONE, MUST MEET AMS 2814 PACKAGING RREQUIREMENTS FOR PREMIUM QUALITY SPOOLED WIRE.
- 3) WELD WIRE INDICATING REQUIREMENTS OF ONLY **AMS 2813** MUST MEET **AMS 2813** STANDARD METHOD PACKAGING REQUIREMENTS WITH WIRE VACUUM PACKED.
- 4) EACH SPOOL OF WIRE MUST BE INDELIBLY MARKED WITH THE MATERIAL TYPE, MATERIAL AMS NUMBER OR GE SPECIFICATION NUMBER, HEAT LOT NUMBER, SIZE AND PURCHASE ORDER ON BOTH SIDES OF THE SPOOL.
- 5) ALL PACKAGED SPOOLS ARE TO BE BE STORED AND SHIPPED IN CARDBOARD CONTAINERS.